

## BL-7000EXT \$1,575

### Extended Length Portable Car Lift System

The BL-7000EXT portable car lift has been redesigned to accommodate vehicles with longer wheelbases. We've increased the overall frame length and lift point spread by 6". As a result, the minimum lift point spread is now 6" longer, as well. Our new portable car lift design better accommodates longer wheelbases and extended lift point spreads.

**Complete package includes;** (2) ea. jack frame assemblies, (2) ea. 150" hydraulic hoses, (2) ea. 14" aux. hoses, (2) ea. quick-mount handles, (4) ea. 2" x 3" x 4" rubber lifting blocks, (4) ea. 3" x 3" x 4" rubber lifting blocks, (1) mini hydraulic power unit with pendant control.

### Notable design features...

- 7,000-pound lifting capacity
- Extended length frames and lifting point spread
- From stow to go in less than 60-seconds
- Dual-position safety locks engage automatically as the lift rises
- Dual locking positions – mid level and full rise
- Extended, cantilevered rubber block trays provide increased rubber block reach
- Portable power unit features a remote push-button control for simple operation
- Steel mounted urethane wheels provide effortless rolling of jack frames on floor
- Remote pendant control features a 13-foot cord
- Power unit features a built-in hydraulic flow divider for precise equalized lifting
- Open-center design for clear under car access
- Quick-connect/disconnect hoses for fast and convenient set-up
- Convenient handles allow for easy positioning of the jack frames
- Strong 14-gauge welded steel frames
- Hydraulic cylinders feature integrated velocity-fuse safety valves
- Includes an eight piece set of adjustable and stackable rubber lift blocks
- Durable powder coat finish



### What's the difference between SLX and EXT?

- SLX minimum lift point spread: 29.5"
- **EXT minimum lift point spread: 37.4"**
  
- SLX maximum lift point spread: 60"
- **EXT maximum lift point spread: 66"**
  
- SLX overall frame length: 71"
- **EXT overall frame length: 76.5" (7000 model only)**



# QuickJack™ Specification Comparison

Specifications are subject to change without notice. Prices may not reflect current promotions.

MODEL	BL-3500SLX	BL-5000SLX	BL-5000EXT	BL-7000SLX	BL-7000EXT
PRICE	\$1,150	\$1,365	\$1,420	\$1,525	\$1,575
LIFTING CAPACITY	3,500 lbs. / 1,588 kg.	5,000 lbs. / 2,268 kg.	5,000 lbs. / 2,268 kg.	7,000 lbs. / 3,175 kg.	7,000 lbs. / 3,175 kg.
COLLAPSED HEIGHT	3" / 76 mm.	3" / 76 mm.	3" / 76 mm.	3.6" / 91 mm.	3.6" / 91 mm.
LIFTING HEIGHT (FRAME ONLY)	16.5" / 419 mm.	17.6" / 447 mm.	17.6" / 447 mm.	18.2" / 462 mm.	18.2" / 462 mm.
LIFTING HEIGHT (SMALL BLOCK)	17" / 432 mm.	18.4" / 467 mm.	18.4" / 467 mm.	18.6" / 471 mm.	18.6" / 471 mm.
LIFTING HEIGHT (TALL BLOCK)	18.5" / 470 mm.	19.2" / 487 mm.	19.2" / 487 mm.	19.4" / 493 mm.	19.4" / 493 mm.
LIFTING HEIGHT (STACKED BLOCKS)	20" / 508 mm.	21.3" / 542 mm.	21.3" / 542 mm.	21.6" / 548 mm.	21.6" / 548 mm.
FRAME WIDTH	10.6" / 268 mm.	11" / 278 mm.	11" / 278 mm.	12.5" / 318 mm.	12.5" / 318 mm.
MAX LIFTING POINT SPREAD	50.5" / 1,283 mm.	60" / 1,524 mm.	66" / 1,676 mm.	60" / 1,524 mm.	66" / 1,676 mm.
MIN LIFTING POINT SPREAD	26.7" / 678 mm.	29.5" / 749 mm.	35.5" / 902 mm.	29.5" / 749 mm.	37.4" / 951 mm.
OVERALL FRAME LENGTH	62" / 1,575 mm.	70" / 1,778 mm.	75" / 1,905 mm.	71" / 1,803 mm.	76" / 1,930 mm.
INDIVIDUAL FRAME WEIGHT	60 lbs. / 27 kg.	76 lbs. / 35 kg.	80 lbs. / 36 kg.	96 lbs. / 44 kg.	101 lbs. / 46 kg.
SHIPPING WEIGHT	180 lbs. / 82 kg.	212 lbs. / 96 kg.	220 lbs. / 100 kg.	242 lbs. / 110 kg.	262 lbs. / 119 kg.
	<a href="#">Learn More</a>	<a href="#">Learn More</a>	<a href="#">Learn More</a>	<a href="#">Learn More</a>	<a href="#">Learn More</a>